



ISTITUTO ITALIANO DI
GARANZIA DELLA QUALITÀ

EC certificate of conformity **1608 CPD P094**

In compliance with the Directive 89/106/EEC of the Council of the European Communities of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to the construction products (Construction Products Directive - CPD), amended by the Directive 93/68/EEC of the Council of the European Communities of 22 July 1993, this is to state that the product:

Vehicle restraint system X-TENSION 110 and X-TENSION 110 DS Terminals

whose performance under impact is detailed in the attached annex

placed on the market by:

Snoline Spa

Via F. Baracca, 19/23 20056 Trezzo s/Adda MI - IT

and manufactured in the factory:

Trezzo d'Adda MI -IT

is submitted by the manufacturer to a factory production control system (FPC) and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the notified body IGQ has performed the initial type-testing for the relevant characteristics of the products, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in Annex ZA of the standard:

EN 1317-5:2007+A1:2008

have been applied and that the products fulfill all the prescribed requirements.

first issue: **15/12/2009**

current issue: **31/08/2010**

Ing. Dario Agalbato
Director

This certificate remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not significantly modified.



ISTITUTO ITALIANO DI
GARANZIA DELLA QUALITÀ

APPENDIX TO CERTIFICATE **1608 CPD P094**

Performance under impact of

X-TENSION 110 and X-TENSION 110 DS Terminals

Product name	Type of test ¹⁾	Performance level	Impact severity	Lateral displacement	Exit box	Durability
X-TENSION 110	TT 1.3.110	P4	A	D.1.1	Z2	Hot dipped galvanized steel components in accordance with UNI ISO 1461
X-TENSION 110	TT 2.1.100	P4	B	D.1.1	Z2	
X-TENSION 110	TT 4.3.110	P4	A	D.1.1	Z1	
X-TENSION 110	TT 5.1.100	P4	A	D 1.1	Z1	
X-TENSION 110 DS	TT 2.1.100	P4	B	D.1.1	Z2	

1) According to ENV 1317-4:2001

first issue : **15/12/2009**
current issue: **31/08/2010**

Ing. Dario Agalbato
Director